

420W 光束灯透镜王+LED 光圈（4 个透镜组合）

参数电源：AC100-240V，50/60Hz

额定功率：600W

灯泡型号：420W，31 颗 0.5WRGB 三合一 LED

光通量为 7950lm，色温可达 8500K, 152mm 出光口径

镇流器：电子电感镇流器

控制方式：DMX512/声控/自走/RDM

通道：18/22 通道

漂亮的点阵显示, 四个轻触百奇按键开关, 可倒转 180° 显示

颜色盘: 一个颜色盘，每个颜色盘由 14 个色片组成+白色，旋转速度可调，双向流水效果及彩虹效果。

图案盘: 固定图案盘，14 个图案效果+白光（含 4 个波图效果）

棱镜 1：一个大角度 12 棱镜，棱镜 2：24 蜂窝棱镜, 棱镜 3：48 蜂窝棱镜，4 棱镜：一个 6 排镜，

可叠加可双向独立旋转

双向旋转，旋转速度可调+七彩虹效果。

调焦：线性调焦，由近至远。

具有雾化功能，

0—100%机械调光，支持机械频闪和可调速频闪效果，支持频闪宏功能，机械频闪为 1-12 F.P.S。

镜头组光学系统, 电动对焦，光束角 0~4°

采用光电复位系统，当偶然发生误动后，可自动检索复位

水平 540°，8Bit/16Bit 微调

垂直 270°，8Bit/16Bit 微调

具有水平、垂直精细自动纠错功能。

过热保护

IP 防护等级: IP20

关电源。

液晶显示屏。

裸灯尺寸：55 *31*25cm

净重：13.2KG

纸箱尺寸：56*38*44cm

毛重：16kg

Parameter power supply: AC100-240V, 50/60Hz

Rated power: 600W

Light bulb model: 420W, 31 0.5W RGB three in one LEDs

The luminous flux is 7950lm, the color temperature can reach 8500K, and the output aperture is 152mm

Ballast: electronic inductor ballast

Control mode: DMX512/voice control/self-propelled/RDM

Channel: 18/22 channels

Beautiful dot matrix display, with four touch sensitive Baiqi button switches that can be reversed 180 ° for display

Color palette: One color palette, each consisting of 14 color chips+white, adjustable rotation speed, bidirectional flowing effect and rainbow effect.

Pattern plate: Fixed pattern plate, 14 pattern effects+white light (including 4 waveform effects)

Prism 1: a large angle 12-prism, Prism 2:24 honeycomb prism, Prism 3:48 honeycomb prism, 4-prism: a 6-row mirror,

Stackable and capable of bidirectional independent rotation

Bidirectional rotation, adjustable rotation speed+rainbow effect.

Focusing: Linear focusing, from near to far.

Equipped with atomization function,

0-100% mechanical dimming, supports mechanical strobe and adjustable strobe effects, supports strobe macro function, mechanical strobe is 1-12 F.P.S.

Lens group optical system, electric focusing, beam angle 0-4 °

Adopting a photoelectric reset system, the reset can be automatically retrieved in case of accidental misoperation

Horizontal 540 ° , 8Bit/16Bit fine-tuning

Vertical 270 ° , 8Bit/16Bit fine-tuning

It has horizontal and vertical fine automatic error correction functions. overheat protection

IP protection level: IP20

Power off.

LCD display screen.

Bare lamp dimensions: 55 * 31 * 25 cm

Net weight: 13.2KG

Carton dimensions: 56*38*44cm

Gross weight: 16kg