

Light source: Ushio 420 long-life gas discharge bulb

Color temperature: 7800K

Diameter of light outlet: 160mm

Illumination: 230000Lux@15m

Light source life: 3000 hours

Beam angle: 1.6°

Effect:

Horizontal scan: 540°

Vertical scan: 270°

Color system: One color wheel, 13 colors plus white light

Gobo system: One fixed gobo plate, 17 gobos

Focus: Electric focus

Atomization: Atomized glass

Strobe: 0~20Hz

Dimming: 0~100% strobe dimming

Prism: One 8-prism, one honeycomb prism, can be superimposed

Control:

Control mode: DMX512 /RDM

DMX channel: 18CH

Display: Touch control interface, can remotely control the bulb switch function, display fan speed, bulb usage time

Power supply:

Input voltage and frequency: 90~240V, 50/60Hz

Power connection: Waterproof power connector input/output

Signal connection: 3 pin or 5 pin waterproof plug socket

Total power: 550W

Power factor: 0.95

Working environment: -20°C~45°C

Physical characteristics:

Size: 41.5*24*70.6CM

Weight: 21kg

Cooling system: air cooling + die-cast magnesium alloy + radiator

Casing: magnesium alloy casing, black outdoor paint

Protection level: IP66

Standard configuration: folding integrated hook, power cable 1PC, DMX cable 1PC, safety rope 1PC

IP rating: IP66