

NEW-380w 光束摇头灯

电源: AC100-240V, 50/60Hz

总功率: 600W

灯泡型号: 380W 光束灯泡

光通量为 7950lm, 色温可达 8500K

镇流器: 电子电感镇流器

控制方式: DMX512/WDMX/自走

通道: 16 通道

漂亮的点阵显示,四个轻触开关,可倒转 180° 显示

颜色盘:一个颜色盘,每个颜色盘由 14 个色片组成+白色,6 片七彩颜色,彩虹效果

旋转速度可调,双向流水效果及彩虹效果。图案盘:固定图案盘,

10 个固定图案+4 个玻图 (14 个图案效果+白光)

棱镜: 48 蜂窝棱镜, 12 棱镜, 双棱镜可叠加可双向独立旋转双向旋转, 旋转速度可调。

调焦: 线性调焦, 由近至远。具有雾化功能, 雾化速度可调。

0—100%机械调光, 支持机械频闪和可调速频闪效果, 支持频闪宏功能, 机械频闪为 1-12 F.P.S。

一个颜色盘,每个颜色盘由 14 个色片组成+白色,旋转速度可调,双向流水效果及彩虹效果°

采用光电复位系统, 当偶然发生误动后, 可自动检索复位

水平 540° , 8Bit/16Bit 微调

垂直 270° , 8Bit/16Bit 微调

具有水平、垂直精细自动纠错功能。

过热保护

IP 防护等级:IP20

AC/DC 开关电源。

液晶显示屏。

尺寸: 280×240×530mm

净重: 12Kg

New 380W beam shaking head light

Power supply: AC100-240V, 50/60Hz

Total power: 600W

Bulb model: Phoenix Bubble 380W

The luminous flux is 7950lm, and the color temperature can reach 8500K

Ballast: Electronic Inductive Ballast

Control mode: DMX512/WMDMX/self-propelled

Channel: 16 channels

Beautiful dot matrix display with four light touch switches, capable of reversing 180 ° display

Color palette: A color palette, each consisting of 14 color tiles+white, 6 colorful tiles, rainbow effect

Adjustable rotation speed, bidirectional flowing effect and rainbow effect. Pattern disk: Fixed pattern disk,

10 fixed patterns+4 glass images (14 pattern effects+white light)

Prism: 48 honeycomb prisms, 12 prisms, double prisms can be stacked and rotate independently in both directions, with adjustable rotation speed.

Focusing: Linear focusing, from near to far. Equipped with atomization function and adjustable

atomization speed.

0-100% mechanical dimming, supporting mechanical strobe and adjustable strobe effects, supporting strobe macro function, mechanical strobe is 1-12 F.P.S.

A color palette, each consisting of 14 color patches+white, with adjustable rotation speed, bidirectional flowing effect and rainbow effect

Adopting a photoelectric reset system, it can automatically retrieve the reset in case of accidental misoperation

Horizontal 540 ° , 8Bit/16Bit fine tuned

Vertical 270 ° , 8Bit/16Bit fine tuned

Equipped with horizontal and vertical fine automatic error correction functions.

Overheat protection

IP protection level: IP20

AC/DC switch power supply.

LCD display screen.

Size: 300 x 240 x 530mm

Net weight: 12Kg

Packaging size: 56 * 38 * 44cm

Gross weight: 15Kg